

# Declaration of Performance

no. Sa 260 013 01

pursuant to Annex III to Regulation (EU) no. 305/2011 for the product:

**1. Unique identification code of the product-type:**

MFC Sanfix 200

**2. Type, batch or serial number or other element allowing identification of construction products in accordance with Art. 11, par. 4:**

MFC Sanfix 260, MFC Sanfix 261 - The date of production can be traced via the date printed on the bag.

**3. Intended use or uses of the construction product in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:**

PCC mortar for concrete repairs and repairs it static function, class R3. EN 1504-3: 2005  
Correction principle 3,4 and 7,  
method 3.1,3.3,4.4,7.1,7.22

**4. Name, trade name or registered trade mark and contact address of the manufacturer in accordance with Art. 11, par. 5:**

MFC - MORFICO s.r.o.  
Olbrachtova 1758, 666 03 Tišnov, Czech Republic

**5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art. 12, par. 2:**

Not applicable

**6. System or systems of assessment and verification of constancy of performance of construction products as set out in Annex V:**

System 4, the manufacturer has implemented and maintains a certified quality management system according to ČSN EN ISO 9001

**7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:**

Not applicable

**8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

Not applicable

**9. Declared performance**

Essential characteristics	Performance MFC Sanfix 260	Performance MFC Sanfix 261	Harmonized Technical Specification
Compressive strength	class R3	class R3	
Chloride ion content	≤ 0,05 %	≤ 0,05 %	
Adhesive bond	≥ 1,5 MPa	≥ 1,5 MPa	
Restrained shrinkage/expansion	≥ 1,5 MPa	≥ 1,5 MPa	
Carbonation resistance	≤ ref. concrete	≤ ref. concrete	EN 1504-3:2005
Elastic modulus	≥ 15 GPa	≥ 15 GPa	
Thermal compatibility – Part 1	≥ 1,5 MPa	≥ 1,5 MPa	
Skid resistance	NPD	NPD	
Capillary absorption	≤ 0,5 kg.m <sup>-2</sup> h <sup>0,5</sup>	≤ 0,5 kg.m <sup>-2</sup> h <sup>0,5</sup>	
Reaction to fire	class A1	class A1	
Dangerous substance	NPD	NPD	

**10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.**

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ing. Oldřich Fiala  
technical director

In Tišnov, date 1.7.2013

