

Declaration of Performance

no. Fi 400 013 01

pursuant to Annex III to Regulation (EU) no. 305/2011 for the product: 1. Unique identification code of the product-type: MFC Final 400 2. Type, batch or serial number or other element allowing identifi- MFC Final 410, 411, 412, 413, MFC Final 420, cation of construction products in accordance with Art. 11, par. 4: MFC Final 430 a MFC Final 440 3. Intended use or uses of the construction product in accordance Polymer-modified cement coating material for internal with the applicable harmonized technical specification, as foreseen use in constructions EN 13813:2002 by the manufacturer: 4. Name, trade name or registered trade mark and contact address MFC - MORFICO s.r.o. of the manufacturer in accordance with Art. 11, par. 5: Olbrachtova 1758, 666 03 Tišnov, ČR 5. Where applicable, name and contact address of the authorized - - representative whose mandate covers the tasks specified in Art. 12, par. 2: 6. System or systems of assessment and verification of constancy System 4, the manufacturer has implemenof performance of construction products as set out in Annex V: ted and maintains a certified quality management system according to ČSN EN ISO 9001 7. In case of the declaration of performance concerning a construc- Initial tests of the fire reaction class conducted by AO tion product covered by a harmonized standard: no. 206 - PAVUS, a.s 8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

9. Declared performance

| Essential characteristics | Performance Final 410 | Performance Final 411,412,413 | Performance Final 420 | Performance Final 430 | Performance Final 440 | Harmonized technical specification |
|---------------------------------|--------------------------|----------------------------------|--------------------------|--------------------------|--------------------------|------------------------------------|
| Reaction to fire | A2fl-s1 | A2fl-s1 | A2fl-s1 | A2fl-s1 | A2fl-s1 | EN 13501-1+A1:2009 |
| Release of dangerous substances | CT | CT | CT | СТ | СТ | EN 13813:2002 |
| Water permeability | NPD | NPD | NPD | NPD | NPD | |
| Water vapour permeability | NPD | NPD | NPD | NPD | NPD | |
| Compressive strength | C40 | C40 | C35 | C40 | C40 | EN 13813:2002 |
| Tensile strength in bending | F10 | F10 | F7 | F10 | F7 | EN 13813:2002 |
| Resistance to abrasion | RWA20 | RWA20 | NPD | RWA20 | NPD | EN 13813:2002 |
| Soundproofing | NPD | NPD | NPD | NPD | NPD | |
| Sound absorption | NPD | NPD | NPD | NPD | NPD | |
| Thermal resistance | NPD | NPD | NPD | NPD | NPD | |
| Chemical resistance | NPD | NPD | NPD | NPD | NPD | |

10.The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ing. Oldřich Fiala technical director

In Tišnov, date 1.7.2013